



OUR GLOBAL  
COMPETENCE  
CENTRES

 APOLLO DISPLAY  
TECHNOLOGIES



 DISTEC



 DISPLAY  
TECHNOLOGY



# Datasheet

## Avalue

### EPD-2501

Public Information Display with Intel® Celeron® SoC BGA Processor N3350





## EPD-2501

### Public Information Display (Digital Signage)

- > 25.3" E Ink Black/White/Red/Yellow
- > 25.3" E Ink Gallery™ Plus Full color 55K (Typ.)
- > 25.3" E Ink Kaleido with color 4096
- > Onboard Intel® Celeron® SoC BGA Processor N3350
- > DDR3L 1866MTs SO-DIMM up to 8GB,
- > 2.5" SATA3 SSD 64GB
- > 2 x HDMI, 1 x COM, 2 x LAN, 4 x USB 3.1 (Gen1)
- > Front Cover Glass, Optional PMMA, support IP54
- > Super Slim Bezel Design
- > E Ink SDK / API support
- > Optional WiFi Module
- > Operating Temp 0~40C

#### + Spec

-System Information-	
<b>Processor</b>	Onboard Intel® Celeron® SoC BGA Processor N3350
<b>System Memory</b>	1 x 204-Pin DDR3L 1866MTs SO-DIMM up to 8GB
<b>Board</b>	ECM-APL2 + LT1000 T-CON Board
Storage	
<b>Storage</b>	2.5" SATA3 SSD 64GB
External I/O	
<b>USB Port</b>	4 x USB 3.1 (Gen1 5Gbps)
<b>LAN Port</b>	2 x RJ45 LAN port
<b>Wireless LAN Antenna</b>	mPCIe Wi-Fi/BlueTooth module
Panel	
<b>LCD Size</b>	25.3"
<b>LCD Panel</b>	E Ink EL253TV1 E Ink AC253TT1
<b>Display Type</b>	E Paper Display
<b>Resolution</b>	3200x1800
<b>Touch Screen</b>	2.8 mm Super Clear CG
Wireless Communication	
<b>WLAN</b>	Optional dual-band 2.4/5.0GHz wireless LAN
<b>Bluetooth</b>	Optional Bluetooth 5.0
<b>Ethernet Chipset</b>	Intel® I211AT, 10/100/1000 Base-Tx Gigabit Ethernet Compatible)
Mechanical & Environmental	
<b>Operating Temperature</b>	0 ~ 40°C
<b>Storage Temperature</b>	-25 ~ 60°C
<b>Operating Humidity</b>	5% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	L 607 x W 350 x H 38.8mm
<b>Weight</b>	4.4kg
<b>Vibration Test</b>	1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
<b>Shock Test</b>	10Grms, IEC 60068-2-27, Half Sine, 11ms
<b>Drop Test</b>	ISTA-2A, IEC-60068-2-32 (96.5cm)
<b>IP Rating</b>	Front IP54
<b>Power Requirement</b>	+12V/5A (60W) (accept +12V DC in)
<b>Power Connector</b>	Lockable DC Jack
<b>Color</b>	Black
Software Support	
<b>OS Information</b>	Windows 10 IoT / Linux

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, the UK and the USA. For more information please contact:

## Headquarters

### Germany



### FORTEC Elektronik AG

Augsburger Str. 2b  
82110 Germering

Phone: +49 89 894450-0  
E-Mail: [info@fortecag.de](mailto:info@fortecag.de)  
Internet: [www.fortecag.de](http://www.fortecag.de)

## Fortec Group Members

### Austria



### Distec GmbH Office Vienna

Nuschinggasse 12  
1230 Wien

Phone: +43 1 8673492-0  
E-Mail: [info@distec.de](mailto:info@distec.de)  
Internet: [www.distec.de](http://www.distec.de)

### Germany



### Distec GmbH

Augsburger Str. 2b  
82110 Germering

Phone: +49 89 894363-0  
E-Mail: [info@distec.de](mailto:info@distec.de)  
Internet: [www.distec.de](http://www.distec.de)

### Switzerland



### ALTRAC AG

Bahnhofstraße 3  
5436 Würenlos

Phone: +41 44 7446111  
E-Mail: [info@altrac.ch](mailto:info@altrac.ch)  
Internet: [www.altrac.ch](http://www.altrac.ch)

### United Kingdom



### Display Technology Ltd.

Osprey House, 1 Osprey Court  
Hinchingsbrooke Business Park  
Huntingdon, Cambridgeshire, PE29 6FN

Phone: +44 1480 411600  
E-Mail: [info@displaytechnology.co.uk](mailto:info@displaytechnology.co.uk)  
Internet: [www.displaytechnology.co.uk](http://www.displaytechnology.co.uk)

### USA



### Apollo Display Technologies, Corp.

87 Raynor Avenue, Unit 1  
Ronkonkoma, NY 11779

Phone: +1 631 5804360  
E-Mail: [info@apolloDisplays.com](mailto:info@apolloDisplays.com)  
Internet: [www.apolloDisplays.com](http://www.apolloDisplays.com)