

# Datasheet

## YSL20C-20W Series

**FORTEC**  
UNITED STATES

**FORTEC**  
INTEGRATED

**FORTEC**  
UNITED KINGDOM

---

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. All specifications are subject to change without notice.

---

**YSL20C-20W SERIES**



**Input: 220-240V 50/60Hz**  
**Output Voltage: 12V,24V**  
**Rated Power: 20W max**

**Features**


- Independent Ultrathin Power Supply
- flicker-free Design
- Terminal block for Quick Connection
- Protections: Over Voltage, Overload, Short Circuit
- Class II Protection Design
- ERP :EU2019/2020



**Application**

- LED strips
- LED indoor lighting
- LED decorative lighting
- LED building lighting

**■ Dimensions and Installation**




**YSL20C-20W SERIES**

MODEL DETAIL SPEC.		YSL20C-1201670	YSL20C-2400833
INPUT	Input Voltage:	220-240VAC	
	Range of Input Voltage:	198-264VAC	
	Input Frequency:	50/60Hz	
	Input Current:	0.3AMAX@Full Load	
	Inrush Current:	< 65 Amps at 230VAC/50Hz@full load	
	Leakage Current:	< 0.25mA/240VAC	
	THD (Full load):	< 20%	
	Unload Power Consumption:	< 0.5W	
	Efficiency:	88%	
	Power Factor:	≥0.7@Full Load 220-240VAC	
OUTPUT	DC Voltage:	12V	24V
	Rated Current(Max):	1.67A	0.833A
	Rated Power(Max):	20W	20W
	Voltage Tolerance:	±5%	
	Ripple and Noise:	400mVp-p	400mVp-p
	Line Regulation:	±3%	
	Load Regulation:	±5%	
	Setup, Rise, Hold Up Time:	1s, 10ms/60ms 230VAC @ full load	
ENVIRONMENTAL	Operating Temperature Ta:	-20°C ~ +45°C	
	Storage Temp:	-40°C ~ +85°C	
	Maximum Case Temperature Tc:	+85°C	
	Humidity:	20 ~ 95% RH	
	Lifetime:	>30000hours@ta 40°C	
PROTECTION	Over Load:	Yes , Protection type: Auto Restore Protection type: Hiccup mode, recovers automatically after fault condition is removed	
	Over Voltage:	Yes , Protection type: Auto Restore Protection type: Shut down o/p voltage, re-power on to recover	
	Short Circuit:	Yes , Protection type: Auto Restore	
SAFETY & EMC	Safety Regulations:	EN61347-2-13:2014+A1:2017,EN61347-1:2015+A1:2021;EN62493:2015	
	Withstand Voltage:	I/P-O/P:3750VAC	
	Harmonic:	EN61000-3-2 Class C EN61000-3-3	
	EMI:	Compliance to EN55015	
	EMS:	Compliance to EN61547:2009	
OTHER	MTBF:	200,000 Hours Minimum at Full Load at 25°C Ambient	
	Case Material and Size:	Plastic	
	IP Grade:	IP20	
	Size:	103*35.5*16.5mm	
	Weight:	70g / pcs	
	Packaging:	100PCS/CTN	

**YSL20C-20W SERIES**


**Deduction Curve and Temperature**




**Minus Output and Input Voltage Curves**




**Power Factor (PF) Curves**



**Efficiency Vs Load**



**Wiring Diagram**



**Manufacturer's address:**

Cuijia, Xidian Town, Ninghai, Ningbo 315613, China

Tel: +86-574-87563856

<https://www.yingjiaodriver.com>

# FORTEC

GROUP

---

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, the UK and the USA. For more information please contact:

## FORTEC

GROUP

FORTEC Elektronik AG | Augsburgener Straße 2b | 82110 Germering  
+49 89 894450-0  
[info@fortecag.de](mailto:info@fortecag.de) | [www.fortecag.de](http://www.fortecag.de)

---

## FORTEC

INTEGRATED

FORTEC Integrated GmbH | Augsburgener Straße 2b | 82110 Germering  
+49 89 894363-0  
[info@fortec-integrated.de](mailto:info@fortec-integrated.de) | [www.fortec-integrated.de](http://www.fortec-integrated.de)

## FORTEC

POWER

FORTEC Power GmbH | Lise-Meitner-Straße 3 | 64560 Riedstadt  
+49 6158 8285-0  
[weborder@fortec-power.de](mailto:weborder@fortec-power.de) | [www.fortec-power.de](http://www.fortec-power.de)

## FORTEC

EGYPT

FORTEC Electronic Design and Solution Egypt SMLC | Linx Business Park  
Unit B318 | Smart Village | Giza Governorate  
[info@fortec-integrated.de](mailto:info@fortec-integrated.de) | [www.fortec-integrated.de](http://www.fortec-integrated.de)

Autronic Steuer- und Regeltechnik GmbH | Siemensstraße 17  
74343 Sachsenheim  
+49 7147 24-0  
[vertrieb@autronic.de](mailto:vertrieb@autronic.de) | [www.autronic.de](http://www.autronic.de)

## FORTEC

CZECH REPUBLIC

FORTEC Czech Republic s.r.o. | Přátelství 275 | 330 02 Dýšina  
+49 89 894363-0  
[info@fortec.cz](mailto:info@fortec.cz) | [www.fortec.cz](http://www.fortec.cz)

## FORTEC

UNITED STATES

FORTEC United States, Corp. | 87 Raynor Avenue Unit 1 | Ronkonkoma  
NY | 11779 | +1 631 5804360  
[info@fortec.us](mailto:info@fortec.us) | [www.fortec.us](http://www.fortec.us)

## FORTEC

SWITZERLAND

FORTEC Switzerland AG | Bahnhofstraße 3 | 5436 Würenlos  
+41 44 7446111  
[info@fortec.ch](mailto:info@fortec.ch) | [www.fortec.ch](http://www.fortec.ch)

## FORTEC

UNITED KINGDOM

FORTEC Technology UK Ltd. | Osprey House | 1 Osprey Court  
Hinchingsbrooke Business Park | Huntingdon | Cambridgeshire | PE29 6FN  
+44 1480 411600  
[info@fortec.uk](mailto:info@fortec.uk) | [www.fortec.uk](http://www.fortec.uk)