




FORTEC
GROUP

POS-Line 15.0

High-quality, robust monitors for process automation in industry

One partner, unlimited technology solutions

Product Features

POS-Line 15.0

Robust Monitor Series

Variable front options



Monitor description

- Highly variable industry monitor solution
- robust, slim cover offers all options for integration and various applications and various modern business scenarios
- equipped with industrial displays and designed for long term availability
- light and slim design presents a modern small look
- passive cooling allows operating the system under full load even at high ambient temperatures
- VESA Mounting holes for using as an HMI or mounted on a stand
- Mounting brackets for in-wall mounting
- safety glass available



POS-Line IOT

- featuring the Raspberry Pi CM3+ based TFT platform Artista-IoT
- industrial functions like Real-Time-Clock and others
- Basis configuration: CM3+ | 32GB
- Standard configuration: Raspberry Pi®



POS-Line IQ

- High performance Intel® Celeron® J3455 processor
- 4GB highspeed RAM and an industrial grade SSD with 128 GB memory

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners.

Copyright 2025 FORTEC Integrated GmbH. All specifications are subject to change without notice.

Various accessories are available for POS-Line monitors.

All monitors can be customized according to your specific requirements. Please contact our sales team if you are interested in product modifications or custom designs.

Panel and Housing

	Measure	Description
Panel Diagonal	[mm] / [Inch]	381/ 15
Type		Open -frame monitor (various bezels, TrueFlat glass and touch solutions are available under options)
Resolution	[Pixel]	1024 x 768
Luminance (center)	[cd/m²]	500
Viewing angle (U/ D/ L/ R)	[°]	88/ 88/ 88/ 88
Backlight Number of colors	— [M]	LED 16.7
Active area (H/V)	[mm]	304.1 x 228.1
Contrast ratio		2500:1
Response time (on/off)	[ms]	21
Pixel class		ISO 9241-307 (pixel error class II)
Life time back light until reaching half brightness	[h]	70.000
Continuous operating time	[h] / [d]	24/ 7
Mounting	[mm]	VESA 200 x 100
Storage temperature	[°C] / [°F]	-40 ~ 85 / -40 ~ 185
Storage/ Operating humidity	[%]	10 ~ 90 (non condensing) 20 ~ 90 (non condensing)
Panel orientation		Landscape and Portrait
Location of connectors		Landscape: bottom/ Portrait: left (front view)
Location of OSD buttons		Landscape: bottom/ Portrait: right (front view)
Housing		Powdered Aluminium, black RAL 9005
IP grade		IP 65 on the front if option TrueFlat glass
Conformity		CE, FCC Class A, EU-RoHS
Packaging		Single packaging single packaging, up to 4 via parcel service, from 5 units on cargo pallet (max. 16 packages p.p.)
Package Contents		Safety instructions

POS-Line 15.0



Monitor open frame including two standard brackets



Monitor with TrueFlat glass

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Video PME - VGA, HDMI, Display Port


POS-Line 15.0

Interfaces		1 x VGA, 1 x HDMI, 1 x DisplayPort, 1 x Audio Line-Out, 1 x USB-Remote
Operating temperature	[°C / F°]	-20 ~ 65/ -4 ~ 149
Power supply	[V]	12
Power consumption (typ.)	[Watt]	10
Weight	[kg]	2.2
Dimensions basic device (W x H x D)	[mm]	333.4 x 265.4 x 51.0

Article Name	Order Number	Description
POSL-MO-150-00	MO-41-096	POS-Line 15.0 Monitor basic device open frame
POSL-MO-150-01	MO-41-101	POS-Line 15.0 Monitor with front bezel
POSL-MO-150-02	MO-41-106	POS-Line 15.0 Monitor with front bezel and glass
POSL-MO-150-03	MO-41-111	POS-Line 15.0 Monitor with TrueFlat glass
POSL-MO-150-06	MO-41-116	POS-Line 15.0 Monitor with front bezel and resistive touch

Further information on the individual options can be found in this document under - OPTIONS.

IOT - Raspberry® IoT Controller




POS-Line 15.0

Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Raspberry® PI		CM3+, 32 GB
Operating temperature	[°C/ F°]	-25 ~ 50/ -13 ~ 122
Power supply	[V]	12
Power consumption (typ.)	[Watt]	11
Weight	[kg]	2.3
Dimensions basic device (W x H x D)	[mm]	333.4 x 265.4 x 51.0

Article Name	Order Number	Description
POSL-RP-150-00	MO-41-097	POS-Line 15.0 IoT basic device open frame
POSL-RP-150-01	MO-41-102	POS-Line 15.0 IoT with front bezel
POSL-RP-150-02	MO-41-107	POS-Line 15.0 IoT with front bezel and glass
POSL-RP-150-03	MO-41-112	POS-Line 15.0 IoT with TrueFlat glass
POSL-RP-150-06	MO-41-117	POS-Line 15.0 IoT with front bezel and resistive touch

Further information on the individual options can be found in this document under - OPTIONS.

WebPoster M3 - Website Player

POS-Line 15.0

Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Raspberry® PI		CM3+, 32 GB
Operating temperature	[°C/ F°]	-25 ~ 50/ -13 ~ 122
Power supply	[V]	12
Power consumption (typ.)	[Watt]	11
Weight	[kg]	2.3
Dimensions basic device (W x H x D)	[mm]	333.4 x 265.4 x 51.0

WebPoster M3 is an industrial FHD network player to show websites. It is a special designed FORTEC Integrated OS for Artista IOT monitors.

Firmware is compatible with touchscreen applications.


Article Name	Order Number	Description
POSL-WP-150-00	MO-41-099	POS-Line 15.0 WebPoster basic device open frame
POSL-WP-150-01	MO-41-104	POS-Line 15.0 WebPoster with front bezel
POSL-WP-150-02	MO-41-109	POS-Line 15.0 WebPoster with front bezel and glass
POSL-WP-150-03	MO-41-114	POS-Line 15.0 WebPoster with TrueFlat glass
POSL-WP-150-06	MO-41-119	POS-Line 15.0 WebPoster with front bezel and resistive touch

Further information on the individual options can be found in this document under - OPTIONS.

IQ Celeron - PC Intel® Celeron®



POS-Line 15.0



Interfaces		2 x Gigabit LAN, 4 x USB 3.0, 1 x HDMI, 1 x RS232/422/485
PC		Intel® Celeron® J3455 (1,5GHz/2,3GHz), RAM: 4 GB DDR3L, Storage: min. 120 GB mSATA
Fan		no
Operating temperature	[°C/ F°]	0 ~ 45/ 32 ~ 113
Power supply	[V]	12 - 26
Power consumption (typ.)	[Watt]	19
Weight	[kg]	2.2
Dimensions basic device (W x H x D)	[mm]	333.4 x 265.4 x 51.0

Article Name	Order Number	Description
POSL-IQ-150-00	MO-41-100	POS-Line 15.0 IQ basic device open frame
POSL-IQ-150-01	MO-41-105	POS-Line 15.0 IQ with front bezel
POSL-IQ-150-02	MO-41-110	POS-Line 15.0 IQ with front bezel and glass
POSL-IQ-150-03	MO-41-115	POS-Line 15.0 IQ with TrueFlat glass
POSL-IQ-150-06	MO-41-120	POS-Line 15.0 IQ with front bezel and resistive touch

Further information on the individual options can be found in this document under - OPTIONS.

Options

Name		Front bezel
Finish		Steel, powdered, black RAL 9005
Weight	[kg]	0.50
Dimensions of monitor with option (W x H x D)	[mm]	336.4 x 268.4 x 52.5

Name		Safety glass	TrueFlat glass
Finish		Safety glass TSG, 3mm anti glare	Safety glass TSG, 3mm anti glare, printed black passepartout RAL 9005
IP grade		Front IP 64 in combination with bezel **	Front IP 65**
Weight	[kg]	0.60	1.00
Dimensions of monitor with option (W x H x D)	[mm]	336.4 x 265.4 x 51.0	373.4 x 301.4 x 57.0

Name		Resistive touch
Bazel Glass		Safety glass TSG, 2.2 mm anti glare
Touch points		1
Touch technology		5 wire analogue resistive
IP grade		Front IP 64 in combination with bezel **
Weight	[kg]	0.60
Dimensions of monitor with option (W x H x D)	[mm]	336.4 x 265.4 x 51.0

POS-Line 15.0

Bezel



Front bezel is a metal bezel for the open frame chassis and VESA mount.

Glass | Touch*



Safety glass is an accessory for the open frame chassis. It covers and protects the TFT-panel. TrueFlat glass is a safety glass with round corners and passepartout for the open frame chassis.

*Glass and touch will reduce monitor brightness.
** depending on the customer's installation

Accessories

Product	Order no.	Product description
Additional RS 232 port	DS-91-823	2nd RS 232 port for IQ Celeron®

Product	Order no.	Product description
VESA adapter plate	DS-91-797	Adaption from VESA 200 x 100 to VESA 100 x 100 for all versions
Mounting brackets	DS-91-356	Set of two additional mounting brackets, not available for option Front bezel - two sets possible for 15.0 inch

Product	Order no.	Product description
Power supply 60 W	NT-01-062	12V/ 5A power supply, max. op. temperature 45°C
Power cord EU	DB-07-225	Power cord EU 1,8 m
Power cord UK	DB-07-226	Power cord UK 1,8 m
Power cord USA	DB-07-238	Power cord USA 1,8 m
Cable VGA	KA-40-053	VGA cable HDDS 15pin. male/ male 1.8 m
Cable DisplayPort	DS-50-571	Cable Display Port male/ male 2 m


Product	Order no.	Product description
WIN 10 IOT Celeron®	DS-60-899	Embedded operation system 2019 LTSC
OS IoT Raspberry® PI	DS-60-859	for POS-Line IoT

Windows 10 IoT Enterprise is a full version of Windows 10 that provides enterprise manageability and security for embedded devices and IoT solutions such as medical devices, industrial automation, measurement systems, and more. It's a binary equivalent of Windows 10 Enterprise, so you can use the same familiar development and management tools as you would on client PCs and laptops. The embedded version of Windows 10 IoT Enterprise is supported by Microsoft for at least 10 years.

POS-Line 15.0

Electronic

Mount



Mounting brackets

Power Supply | Cable

Software

Our corporate network supports you worldwide with branches in Germany, Austria, Switzerland, Czech Republic, Benelux, the UK, the USA, and Egypt. For further information, please contact us:

CONTACT

FORTEC GROUP

FORTEC Elektronik AG | Augsburger Str. 2b | 82110 Germering
+49 89 894450-0 | info@fortecag.de | www.fortecag.de

FORTEC INTEGRATED

FORTEC Integrated GmbH | Augsburger Str. 2b | 82110 Germering
+49 89 894363-0 | info@fortec-integrated.de | www.fortec-integrated.de

FORTEC UNITED KINGDOM

FORTEC Technology UK Ltd. | Osprey House | 1 Osprey Court
Hinchingsbrooke Business Park | Huntingdon | Cambridgeshire | PE29 6FN
+44 1480 411600 | info@fortec.uk | www.fortec.uk

FORTEC EGYPT

FORTEC Electronic Design and Solutions Egypt SMLC | Linx Business Park | Unit B318
Smart Village | Giza Governorate
+20 120 1146222 | info@fortec.eg | www.fortec.eg

FORTEC CZECH REPUBLIC

FORTEC Czech Republic s.r.o. | Přátelství 275 | 330 02 Dýšina
+420 377 845878 | fortec@fortec.cz | www.fortec.cz

FORTEC POWER

FORTEC Power GmbH | Lise-Meitner-Straße 3 | 64560 Riedstadt
+49 6158 8285-0 | weborder@fortec-power.de | www.fortec-power.de

FORTEC UNITED STATES

FORTEC US, Corp. | 87 Raynor Avenue Unit 1 | Ronkonkoma | NY | 11779
+1 631 5804360 | info@fortec.us | www.fortec.us

FORTEC SWITZERLAND

FORTEC Switzerland AG | Bahnhofstraße 3 | 5436 Würenlos
+41 44 7446111 | info@fortec.ch | www.fortec.ch

FORTEC BENELUX

FORTEC Benelux B.V. | Everdenberg 79 | 4902 TT Oosterhout | North Brabant
+31 162 515458 | info@fortec-benelux.com | www.fortec-benelux.com