

PRELIMINARY

FORTEC GROUP

PLUS-Line 64.5

Multifunctional and optimally designed 4K Monitors

One partner, unlimited technology solutions

Product Features

Designed, developed and made in Germany

PLUS-Line 64.5





PLUS-Line combines the entire experience of FORTEC GROUP in monitor construction with the wishes of the company's customers. It offers a large 4K panel a professional framework and with this line brings a slim touchscreen. A dockable PC module complete the PLUS-Line.

Example meeting room

- → The perfect tool for the new way of collaboration
- → Intelligent cooling without fan
- → Attractive, slim design
- → metal housing instead of plastic
- → very good brightness and anti-reflective glass for ideal glare-free view
- → super thin touch sensor
- → IP65 front with the option TrueFlat glass or touch and corresponding installation by the customer
- → Maintenance friendly - the relevant components can be replaced quickly
- → version with Box PC

Options:

- → Front Bezel
- → TrueFlat glass | extremely narrow passepartout
- → TrueFlat glass touch | extremely narrow passepartout
- → 55" all around 25.5 mm passepartout

Perfect multimedia conference tool

WLAN remote integrated

Thin touch screen

Small sustainable design

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners.

Copyright 2025 FORTEC Integrated GmbH. All specifications are subject to change without notice.

Panel, Housing and Electric

PLUS-Line 64.5

		64.5 inch
Panel Diagonal	[mm] / [Inch]	1638/ 64.5
Type		Monitor open frame
Resolution	[Pixel)	3.840 x 2.160 (4K)
Luminance (cent./typ)	[cd/m²]	700
Viewing angle (U/ D/ L/ R)	[°]	89/ 89/ 89/ 89
Backlight | Number of colors	— | [M]	LED | 16.7
Active area (H/V)	[mm]	1428.5 x 803.5
Contrast ratio | Resp. time (on/off)	— | [ms]	4000 : 1 | 6.5
Life time back light until reaching half brightness	[h]	50.000
Contin. operating time	[h] / [d]	24/ 7
Monitor control		via OSD menu
Power supply	[VAC]	100-240~; 50/60 Hz
Storage temperature	[°C] / [°F]	-20 ~ 60/ -4 ~ 140
Operation temperature	[°C] / [°F]	0 ~ 40/ 32 ~ 104
Storage | Operation humidity	[%]	10 ~ 90 (non condensing)
Housing		Powdered steel, color DB-703 smooth matte
IP65		Front IP 65 with option TrueFlat glass or TrueFlat touch
Mounting	[mm]	VESA MIS-F 800 x 600 (4 x M8)
Panel Orientation		Landscape and Portrait
Location of connectors		Landscape: middle backside | Portrait: left backside (front view)
Location of OSD buttons		Landscape: bottom right | Portrait: bottom left (front view)
Confirmity		CE, FCC Class A, EU-RoHS
Packaging		Single packaging for transport per pallet, max. 2 pcs. per pallet
Package Contents		Safety instructions, power cable



PLUS-Line 64.5 front view




PLUS-Line 64.5 backside with PC

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON" for approximately 30 minutes at an ambient temperature of 25° C (77° F).
Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Prisma P4K - HDMI, Display Port

PLUS-Line 64.5



TUIO (Tangible User Interface Object) is an open protocol for the communication of data from devices.
It is used to switch USB ports and their functions (such as webcam or microphone) between internal and external use. This switch is only available on P4K with Mediabar.

Interfaces		2x HDMI in, 1x DP in, 1 x USB-B (Remote), 1 x Line out, 1 x Infrared Sensor
Power consumption (typ.)	[Watt]	tdb
Weight	[kg]	tdb
Dimensions basic device (W x H x D)	[mm]	1487 x 862 x 93.3
Package Contents		Remote Control




PLUS-Line 64.5 front view

Order Number	Description
MO-41-084	PLUS-Line 64.5 Monitor P4K basic device open frame
MO-41-237	PLUS-Line 64.5 Monitor P4K with front bezel
MO-41-085	PLUS-Line 64.5 Monitor P4K with TrueFlat glass
MO-41-086	PLUS-Line 64.5 Monitor P4K with TrueFlat glass with PCAP TS

Further information on the individual options can be found in this document under - OPTIONS.

IOT - Raspberry® IoT Controller

PLUS-Line 64.5



Interfaces		1 x LAN, 2 x USB, 1 x Micro HDMI in, 1 x Micro HDMI out, 1 x Line out, 1 xUSB-C Config, 1 x USB-C Linux console, 1 x Infrared Sensor
Raspberry® PI		CM4, 32 GB
Power consumption (typ.)	[Watt]	tbd
Weight	[kg]	tbd
Dimensions basic device (W x H x D)	[mm]	1487 x 862 x 93.3
Package Contents		Remote Control




PLUS-Line 64.5 backside without PC

Order Number	Description
MO-41-093	PLUS-Line 64.5 IoT basic device open frame
MO-41-240	PLUS-Line 64.5 IoT with front bezel
MO-41-094	PLUS-Line 64.5 IoT with TrueFlat glass
MO-41-095	PLUS-Line 64.5 IoT with TrueFlat glass with PCAP TS

Further information on the individual options can be found in this document under - OPTIONS.

WebPoster M3 - Website Player

PLUS-Line 64.5



WebPoster M4 is an industrial 4K | UHD network player to show websites. It is a special designed FORTEC Integrated OS for Artista IOT monitors.

Firmware is compatible with touchscreen applications.


Interfaces		1 x LAN, 2 x USB, 1 x Micro HDMI in, 1 x Micro HDMI out, 1 x Line out, 1 xUSB-C Config, 1 x USB-C Linux console, 1 x Infrared Sensor
Power consumption (typ.)	[Watt]	tbd
Weight	[kg]	tbd
Dimensions basic device (W x H x D)	[mm]	1487 x 862 x 93.3
Package Contents		Remote Control

Order Number	Description
MO-41-090	PLUS-Line 64.5 WebPoster basic device open frame
MO-41-239	PLUS-Line 64.5 WebPoster with front bezel
MO-41-091	PLUS-Line 64.5 WebPoster with TrueFlat glass
MO-41-092	PLUS-Line 64.5 WebPoster with TrueFlat glass with PCAP TS

Further information on the individual options can be found in this document under - OPTIONS.

IQ i5 - PC Intel®

PLUS-Line 64.5





PLUS-Line 64.5 IQ, front



PLUS-Line 64.5 IQ, backside with PC

Interfaces		1x DP, 2x LAN, 3x USB 3.2, 2x USB 2.0 1x USB C, 1x RS232, 1x RS232/422/485, 1x Audio in/ out, 1x MIC in
PC		CPU: Intel® Core™-i5- 1145G7E (4 x 1.5 - 4.1 GHz), Intel® Iris® X^{E}, 2 x 4 GB DDR 4 RAM, 128 GB M.2Sata
Fan		passive
Power consumption (typ.)	[Watt]	tdb
Weight	[kg]	tbd
Dimensions basic device (W x H x D)	[mm]	1487 x 862 x 114.4

Order Number	Description
MO-41-229	PLUS-Line 64.5 IQ basic device open frame
MO-41-241	PLUS-Line 64.5 IQ with front bezel
MO-41-230	PLUS-Line 64.5 IQ with TrueFlat glass
MO-41-231	PLUS-Line 64.5 IQ with TrueFlat glass with PCAP TS

Further information on the individual options can be found in this document under - OPTIONS.

Options

PLUS-Line 64.5

Electronic

Order number	PC-61-204
Name	PC Box extern Plus-Line IQ-i5
Description	PC Module for external mounting
Interfaces	1x DP, 2x LAN, 3x USB 3.2, 2x USB 2.0 1x USB C, 1x RS232, 1x RS232/422/485, 1x Audio, 1x MIC in
PC	CPU: Intel® Core™-i5- 1145G7E (4 x 1.5 - 4.1 GHz), Intel® Iris® X^E, 2 x 4 GB DDR 4 RAM, 128 GB M.2 Sata
Fan	passive
Weight [kg]	2.2
Dimensions [mm]	211 x 150.50 x 63.10

Glass | Touch*

*Glass and touch screens will reduce monitor brightness.

Name		TrueFlat glass
Finish		Glass TSG 4.0 mm, small passepartout RAL 9005
Weight	[kg]	13.5
Dimensions of monitor with option (W x H x D)	[mm]	1487 x 862 x 93.3 (IQ 114.4)

Name		TrueFlat Touch
Touch		Capacitive touch, 20 points, up to 4 active touch pens poss. , 120 Hz sampling rate
Finish		Glass TSG 4.0 mm, small passepartout RAL 9005
Weight	[kg]	14.0
Dimensions of monitor with option (W x H x D)	[mm]	1487 x 862 x 93.3 (IQ 114.4)

Bezel

Name		Front bezel
Finish		Powdered steel, Sparkling iron effect dark, metallic fine structure matt, near RAL 7024
Weight	[kg]	1.8
Dimensions of monitor with option (W x H x D)	[mm]	1492 x 867 x 94.3 (IQ 114.4)

Accessories

PLUS-Line 64.5

Mount

Product	Order no.	Product description
Wall mount	MO-41-XXX	fixed wall mount for PLUS-Line 64.5

Electronic

Product	Order no.	Product description
IR Remote Control	DS-92-258	IR sensor with remote control for PLUS-Line 54.6 and 64.5
Cable DP for PC box	KA-40-115	DP cable for connection PC, 0,5m

Software

Product	Order no.	Product description
Windows 11 IOT 2024 LTSC (ePKEA) Value+zDM	SW-60-048	Embedded operation system DE/ EN for Core-i

Windows 11 IoT Enterprise is a full version of Windows 11 that provides enterprise manageability and security for embedded devices and IoT solutions such as medical devices, industrial automation, measurement systems, and more. It's a binary equivalent of Windows 11 Enterprise, so you can use the same familiar development and management tools as you would on client PCs and laptops. The embedded version of Windows 11 IoT Enterprise is supported by Microsoft for at least 10 years.

Our corporate network supports you worldwide with branches in Germany, Austria, Switzerland, the United Kingdom, the Netherlands, the Czech Republic, Egypt, and the United States. For further information, please contact:

CONTACT

FORTEC GROUP

FORTEC Elektronik AG | Augsburger Str. 2b | 82110 Germering
+49 89 894450-0 | info@fortecag.de | www.fortecag.de

FORTEC INTEGRATED

FORTEC Integrated GmbH | Augsburger Str. 2b | 82110 Germering
+49 89 894363-0 | info@fortec-integrated.de | www.fortec-integrated.de

FORTEC POWER

FORTEC Power GmbH | Lise-Meitner-Straße 3 | 64560 Riedstadt
+49 6158 8285-0 | weborder@fortec-power.de | www.fortec-power.de

FORTEC UNITED KINGDOM

FORTEC Technology UK Ltd. | Osprey House | 1 Osprey Court
Hinchingbrooke Business Park | Huntingdon | Cambridgeshire | PE29 6FN
+44 1480 411600 | info@fortec.uk | www.fortec.uk

FORTEC UNITED STATES

FORTEC US, Corp. | 87 Raynor Avenue Unit 1 | Ronkonkoma | NY | 11779
+1 631 5804360 | info@fortec.us | www.fortec.us

FORTEC EGYPT

FORTEC Electronic Design and Solutions Egypt SMLC| Linx Business Park | Unit B318
Smart Village | Giza Governorate
+20 120 1146222 | info@fortec.eg | www.fortec.eg

FORTEC SWITZERLAND

FORTEC Switzerland AG | Bahnhofstraße 3 | 5436 Würenlos
+41 44 7446111 | info@fortec.ch | www.fortec.ch

FORTEC CZECH REPUBLIC

FORTEC Czech Republic s.r.o. | Přátelství 275 | 330 02 Dýšina
+420 377 845878 | fortec@fortec.cz | www.fortec.cz

FORTEC BENELUX

FORTEC Benelux B.V. | Everdenberg 79 | 4902 TT Oosterhout | North Brabant
+31 162 515458 | info@fortec-benelux.com | www.fortec-benelux.com